

CRIMPING TABLE

DN	5	6	8	10	12	16	19	25	32	38	51
INCH	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1.1/4	1.1/2	2

HOSE EN 853 1SN SAE 100 R1AT (PH253..)

Boccola / Ferrule	800101	800102	800103	800104	800105	800106	800107	800108	800109	800110	800111
D1 - D2 - L1	16 - 9,9 - 23,5	19 - 12,4 - 25,5	21 - 14 - 26,5	23 - 16,3 - 27	28 - 19,8 - 29	31 - 23 - 32	35 - 27,1 - 36	42 - 34 - 44,5	50 - 41,6 - 48	56 - 47,9 - 55	70 - 61,2 - 63
Ø pressatura Crimping	13.8	15.0	17.6	19.3	23.6	26.3	30.1	36.9	45.2	50.8	65
Lungh. spellicciatura Skiving length	16	18	17,5	18,5	19,5	22,5	25	32	33,5	39	45,5
Tubo / Hose	PH253-03	PH253-04	PH253-05	PH253-06	PH253-08	PH253-10	PH253-12	PH253-16	PH253-20	PH253-24	PH253-32
Boccola / Ferrule	800301	800302	800303	800304	800305	800306	800307	800308	800309	800310	-
D1 - D2 - L1	18 - 12,2 - 23,5	19 - 13,8 - 25,5	21 - 15,5 - 26,5	23 - 17,7 - 27	27,5 - 21,2 - 29	31 - 24,4 - 32	35 - 28,3 - 36	42 - 36,1 - 44,5	51 - 44,5 - 48	58 - 51,2 - 55	-
Ø pressatura Crimping	14.4	15.8	17.6	19.9	23.4	26.6	30.3	38.9	45.8	52.8	-
Lungh. spellicciatura Skiving length	-	-	-	-	-	-	-	-	-	-	-
Tubo / Hose	PH253-03	PH253-04	PH253-05	PH253-06	PH253-08	PH253-10	PH253-12	PH253-16	PH253-20	PH253-24	-
Boccola / Ferrule	800551	800552	800553	800554	800555	800556	800557	800558	800559	800560	800561
D1 - D2 - L1	20,5 - 13,8 - 23,5	22,5 - 15,4 - 25,5	23,5 - 17 - 26,5	25 - 19,4 - 27	28 - 22,6 - 29	32 - 25,9 - 32	36 - 29,7 - 36	45 - 38,3 - 44,5	57 - 48,4 - 47	65 - 55,3 - 58	78 - 68,2 - 66,5
Ø pressatura Crimping	15.8	17.7	19.5	20.1	22.8	26.1	30.2	37.3	46.4	53.8	67
Lungh. spellicciatura Skiving length	-	-	-	-	-	-	-	-	-	-	-
Tubo / Hose	PH253-03	PH253-04	PH253-05	PH253-06	PH253-08	PH253-10	PH253-12	PH253-16	PH253-20	PH253-24	-

HOSE EN 853 2SN SAE 100 R2AT (PH254..)


Boccola / Ferrule	800201	800202	800203	800204	800205	800206	800207	800208	800209	800210	800211
D1 - D2 - L1	19 - 11,7 - 23,5	20 - 13,4 - 25,5	23 - 15,4 - 26,5	24,5 - 17,8 - 27	29 - 21,1 - 29	33 - 24,3 - 32	37 - 28,3 - 36	45 - 35,8 - 44,5	55 - 45,2 - 48	61 - 51,5 - 55	74 - 64,6 - 63
Ø pressatura Crimping	16.4	16.6	19.7	20.7	24.9	29.2	32.6	39.8	49.5	55.5	69.2
Lungh. spellicciatura Skiving length	16	18	17,5	18,5	19,5	22,5	25	32	33,5	39	45,5
Tubo / Hose	PH254-03	PH254-04	PH254-05	PH254-06	PH254-08	PH254-10	PH254-12	PH254-16	PH254-20	PH254-24	PH254-32
Boccola / Ferrule	800401	800402	800403	800404	800405	800406	800407	800408	800409	800410	-
D1 - D2 - L1	20 - 13,8 - 23,5	21 - 15,4 - 25,5	23 - 17 - 26,5	24,5 - 19,4 - 27	28 - 22,6 - 29	32 - 25,9 - 32	36 - 29,7 - 36	45 - 38,3 - 44,5	56 - 49 - 48	64 - 55,3 - 55	-
Ø pressatura Crimping	16.2	16.8	19	20.8	23.4	27.4	31.2	38.9	48.4	56	-
Lungh. spellicciatura Skiving length	-	-	-	-	-	-	-	-	-	-	-
Tubo / Hose	PH254-03	PH254-04	PH254-05	PH254-06	PH254-08	PH254-10	PH254-12	PH254-16	PH254-20	PH254-24	-
Boccola / Ferrule	800551	800552	800553	800554	800555	800556	800557	800558	800559	800560	800561
D1 - D2 - L1	20,5 - 13,8 - 23,5	22,5 - 15,4 - 25,5	23,5 - 17 - 26,5	25 - 19,4 - 27	28 - 22,6 - 29	32 - 25,9 - 32	36 - 29,7 - 36	45 - 38,3 - 44,5	57 - 48,4 - 47	65 - 55,3 - 58	78 - 68,2 - 66,5
Ø pressatura Crimping	16.4	18.5	19.6	21.2	23.9	28.1	31.6	39	49	56.1	69.3
Lungh. spellicciatura Skiving length	-	-	-	-	-	-	-	-	-	-	-
Tubo / Hose	PH254-03	PH254-04	PH254-05	PH254-06	PH254-08	PH254-10	PH254-12	PH254-16	PH254-20	PH254-24	PH254-32


CRIMPING TABLE


DN	5	6	8	10	12	16	19	25	32	38	51
INCH	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1.1/4	1.1/2	2


HOSE EN 857 1SC (PH257..) 	Boccola / Ferrule		800552-COMP	800553-COMP	800554-COMP	800555-COMP						
	D1 - D2 - L1		20 - 14,2 - 25	22 - 16 - 26	24 - 18,2 - 26	27 - 21 - 28						
	Ø pressione Crimping	-	15.2	16.8	18.3	21.9	-	-	-	-	-	-
	Lungh. spellicciatura Skiving length		-	-	-	-						
Tubo / Hose			PH257-04	PH257-05	PH257-06	PH257-08						

HOSE EN 857 2SC (PH258..) 	Boccola / Ferrule		800102	800103	800104	800105	800106	800107	800108			
	D1 - D2 - L1		19 - 12,4 - 25,5	21 - 14 - 26,5	23 - 16,3 - 27	28 - 19,8 - 29	31 - 23 - 32	35 - 27,1 - 36	42 - 34 - 44,5			
	Ø pressione Crimping	-	16	17.9	19.7	24.3	27.4	30.6	37.5	-	-	-
	Lungh. spellicciatura Skiving length		18	17,5	18,5	19,5	22,5	25	32			
Tubo / Hose			PH258-04	PH258-05	PH258-06	PH258-08	PH258-10	PH258-12	PH258-16			

HOSE EN 857 2SC (PH258..) 	Boccola / Ferrule		800302	800303	800304	800305	800306	800307	800308			
	D1 - D2 - L1		19 - 13,8 - 25,5	21 - 15,5 - 26,5	23 - 17,7 - 27	27,5 - 21,2 - 29	31 - 24,4 - 32	35 - 28,3 - 36	42 - 36,1 - 44,5			
	Ø pressione Crimping	-	15.4	17.4	19	23.1	26.9	30.6	38	-	-	-
	Lungh. spellicciatura Skiving length		-	-	-	-	-	-	-			
Tubo / Hose			PH258-04	PH258-05	PH258-06	PH258-08	PH258-10	PH258-12	PH258-16			

HOSE EN 857 2SC (PH258..) 	Boccola / Ferrule		800552	800553	800554	800555	800556	800557	800558			
	D1 - D2 - L1		22,5 - 15,4 - 25,5	23,5 - 17 - 26,5	25 - 19,4 - 27	28 - 22,6 - 29	32 - 25,9 - 32	36 - 29,7 - 36	45 - 38,3 - 44,5			
	Ø pressione Crimping	-	18	18.7	20.3	22	26.2	30.9	37.8	-	-	-
	Lungh. spellicciatura Skiving length		-	-	-	-	-	-	-			
Tubo / Hose			PH258-04	PH258-05	PH258-06	PH258-08	PH258-10	PH258-12	PH258-16			

TUBO / HOSE 1SC HYDRO-WASH COVER BLACK (7314..) 	Boccola / Ferrule		800552-COMP	800553-COMP	800554-COMP							
	D1 - D2 - L1		20 - 14,2 - 25	22 - 16 - 26	24 - 18,2 - 26							
	Ø pressione Crimping	-	15.2	16.8	18.3	-	-	-	-	-	-	-
	Lungh. spellicciatura Skiving length		-	-	-							
Tubo / Hose			731402	731403	731404							

TUBO / HOSE 1SC HYDRO-WASH COVER BLUE (7315..) 	Boccola / Ferrule		800552-COMP	800553-COMP	800554-COMP							
	D1 - D2 - L1		20 - 14,2 - 25	22 - 16 - 26	24 - 18,2 - 26							
	Ø pressione Crimping	-	15.2	16.8	18.3	-	-	-	-	-	-	-
	Lungh. spellicciatura Skiving length		-	-	-							
Tubo / Hose			731502	731503	731504							

CRIMPING TABLE

DN	5	6	8	10	12	16	19	25	32	38	51
INCH	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1.1/4	1.1/2	2

**HOSE
2SC PRESSURE
WASHER COVER
BLACK
(PH522C..BB)**

Boccola / Ferrule		800102	800103	800104							
D1 - D2 - L1		19 - 12,4 - 25,5	21 - 14 - 26,5	23 - 16,3 - 27							
Ø pressione Crimping	-	16	17.9	19.7	-	-	-	-	-	-	-
Lungh. spellicciatura Skiving length		18	17,5	18,5							
Tubo / Hose		PH522C-04BB	PH522C-05BB	PH522C-06BB							

Boccola / Ferrule		800552	800553	800554							
D1 - D2 - L1		22,5 - 15,4 - 25,5	23,5 - 17 - 26,5	25 - 19,4 - 27							
Ø pressione Crimping	-	17.7	18.7	19.7	-	-	-	-	-	-	-
Lungh. spellicciatura Skiving length		-	-	-							
Tubo / Hose		PH522C-04BB	PH522C-05BB	PH522C-06BB							

**HOSE
2SC PRESSURE
WASHER COVER
BLUE
(PH522C..BU)**

Boccola / Ferrule		800102	800103	800104							
D1 - D2 - L1		19 - 12,4 - 25,5	21 - 14 - 26,5	23 - 16,3 - 27							
Ø pressione Crimping	-	16	17.9	19.7	-	-	-	-	-	-	-
Lungh. spellicciatura Skiving length		18	17,5	18,5							
Tubo / Hose		PH522C-04BU	PH522C-05BU	PH522C-06BU							

Boccola / Ferrule		800552	800553	800554							
D1 - D2 - L1		22,5 - 15,4 - 25,5	23,5 - 17 - 26,5	25 - 19,4 - 27							
Ø pressione Crimping	-	17.7	18.7	19.7	-	-	-	-	-	-	-
Lungh. spellicciatura Skiving length		-	-	-							
Tubo / Hose		PH522C-04BU	PH522C-05BU	PH522C-06BU							

**HOSE
EN 856 4SP
(PH277..)**

Boccola / Ferrule		800602		800604	800605	800606	800607	800608			
D1 - D2 - L1		22 - 15,4 - 30		25 - 18,2 - 31	29 - 21,1 - 35	33 - 24,7 - 38	38 - 29,2 - 43	45 - 36,2 - 58			
Ø pressione Crimping	-	18.4	-	21.3	25	29.0	33.8	40.6	-	-	-
Lungh. spellicciatura Skiving length		23		23,5	26	28,5	32	44,5			
Tubo / Hose		PH277-04		PH277-06	PH277-08	PH277-10	PH277-12	PH277-16			

**HOSE
EN 856 4SH
(PH278..)**

Boccola / Ferrule							800607	800608	800609	800610	800611
D1 - D2 - L1							38 - 29,2 - 43	45 - 36,2 - 58	52 - 43 - 64	60 - 49,6 - 72	75 - 64,3 - 81
Ø pressione Crimping	-	-	-	-	-	-	33.8	40.2	47.0	55.0	70
Lungh. spellicciatura Skiving length							32	44,5	49	56	63,5
Tubo / Hose							PH278-12	PH278-16	PH278-20	PH278-24	PH278-32

CRIMPING TABLE

DN	5	6	8	10	12	16	19	25	32	38	51
INCH	3/16	1/4	5/16	3/8	1/2	5/8	3/4	1	1.1/4	1.1/2	2

HOSE
SAE 100 R7
(PH148..)

8008..
No Skive

Boccola / Ferrule	800801	800802	800803	800804							
D1 - D2 - L1	14 - 10,6 - 24	17 - 13,4 - 25,5	19 - 15,2 - 26,5	21 - 16,7 - 27							
Ø pressatura Crimping	11.7	13.8	16	17.9	-	-	-	-	-	-	-
Lungh. spellicciatura Skiving length	-	-	-	-							
Tubo / Hose	PH148-03	PH148-04	PH148-05	PH148-06							

HOSE
R8
(PH348..)

8008..
No Skive

Boccola / Ferrule	800801	800802	800803	800804	800805	800806	800807	800808			
D1 - D2 - L1	14 - 10,6 - 24	17 - 13,4 - 25,5	19 - 15,2 - 26,5	21 - 16,7 - 27	25,5 - 20,8 - 29	28,5 - 24 - 32	32 - 27,5 - 36	40 - 34,5 - 44,5			
Ø pressatura Crimping	11.7	13.9	16.2	18.0	21.9	25.7	27.9	36.1	-	-	-
Lungh. spellicciatura Skiving length	-	-	-	-	-	-	-	-			
Tubo / Hose	PH348-03	PH348-04	PH348-05	PH348-06	PH348-08	PH348-10	PH348-12	PH348-16			